

MOBILE SCAFFOLD TOWER

2.60 TRADE SERIES

Scaffold Solutions 03 9460 1333

Scaffold Solutions manufactures and distributes Aluminium Mobile Towers to the rental industry worldwide

all frames and braces are constructed with extruded 2.6mm aluminium tubing



Frames

- Every Frame is a base frame, building frame and guardrail frame. 100% utilisation of scaffold components
- 2.6mm wall thickness tube
- 48.6mm outside diameter tube (adapts to standard scaffold fittings and jacks)
- Aluminium spigot
- 500mm transom centres
- Additional wall thickness creates longer frame life
- 1m & 1.5m frames incorporates guard rail
- Frame widths 0.7m, 1.2m, 1.8m & 3m
- Full tig welded frame

Braces

- Robust
- 2.6mm wall thickness
- Lock on, Lock off hooks

Wheels

- 200mm castor
- Adjustable

Ladder

- Variable or straight
- Steel ladder hooks
- Aluminium ladder arms

Deck

- Fully bolted assembly design
- Captivated decking complete with anti-slip plywood
- Robust construction

2.60 - SERIES SPECIFICATIONS

Tubes (outside \varnothing)	48.6mm	Alloy	6061T6
Wall Thickness	2.6mm	All Castings	Pressure Die Cast



Scaffold Solutions